



Electro-Voice

THE NEXT-GENERATION OF EVOLVE 30M, 50 & 50M


OWN THE ROOM



EVOLVE^{G2}

SAME SIGNATURE SOUND, WITH MORE OUTPUT

Under the hood, the G2 models answer the most consistent request from the EVOLVE community by raising maximum SPL to 125 dB on the 30M G2 and 129 dB on the 50 and 50M G2 models. That extra headroom covers larger rooms and fuller dance floors, while the precise 120° x 40° coverage pattern delivers even, detailed sound to every listener.



THE ROOM BECOMES YOURS

The slim form factor, a clean visual design with black and white color options make EVOLVE G2 equally at home in a hotel ballroom, a modern worship auditorium, a corporate keynote, or a rooftop event.

The 30M G2 is the ideal companion for smaller venues, ceremonies, and mobile performers. The 50 G2 scales output for mid-sized to large event spaces, while the 50M G2 includes a built-in mixer for solo performers and operators who need more inputs at the source.



UPGRADES IN ALL THE RIGHT PLACES

EVOLVE G2 retains the familiar small footprint, lightweight transport, and the ultra-fast setup that gets a system show-ready in moments. Building on this, the redesigned subwoofer handles on top make load-in and load-out noticeably easier at the end of a long night, while a large full-color LCD provides clearer real-time system feedback at a glance, even under show pressure.



TRANSPORTATION IS ONLY PART OF THE JOURNEY

Every EVOLVE G2 system includes a transport bag to safely carry or store your column array and sub pole. 30M G2: backpack and 50 / 50M G2: shoulder bag.

The redesigned subwoofer slip cover features a top handle flap for easier hauling. Also available are subwoofer roller bags with four casters and telescoping handles. Slip covers and roller bags sold separately.




A MAJOR LEAP FOR MOBILE CONTROL

The QuickSmart App serves as the control center for the EVOLVE G2 range. The latest 3.0 release is a major update of the free app for iOS and Android, delivering a complete UI overhaul and more functionality. Multi-speaker management, True Wireless Stereo (TWS) configuration, and speaker grouping through an improved interface built for fast decisions in live environments. Over-the-air firmware updates keep the system up to date.



EVOLVE 30M G2

Column array	6x 2.8" neodymium drivers
Subwoofer	1x 10"
Frequency response (-3 dB) ¹	51 Hz – 20 kHz
Frequency range (-10 dB) ¹	45 Hz – 20 kHz
Maximum SPL ²	125 dB
Coverage (H x V)	120° x 40°
Amplifier rating ³	1500 W
Connectors	4x XLR/TRS combo jack line / mic inputs 2x XLR/TRS combo jack for stereo line inputs 1x wireless stereo Bluetooth® audio input 1x stereo RCA input 1x 3.5 mm stereo input 1x 1/4" TRS HI-Z input 1x 1/4" footswitch input 1x RJ45 QuickSmart Link connector 1x XLR mix out output 1x XLR aux out output 1x IEC power connector
Screen (diagonally measured)	Full-color 2.9" LCD
Enclosures	Column: composite Pole: aluminum Sub: 15 mm plywood
Grille	Steel with black or white powder coat
Colors	Black or white
Dimensions (H x W x D)	78.5" x 13" x 17" (1995 x 332 x 432 mm)
Net weight	43.5 lbs (19.8 kg)



EVOLVE 50 G2

8x 3.5" neodymium drivers
1x 12"
43 Hz – 20 kHz
37 Hz – 20 kHz
129 dB
120° x 40°
1500 W
2x XLR/TRS combo jack line / mic inputs 1x wireless stereo Bluetooth® audio input 1x stereo RCA input 1x 3.5 mm input 1x RJ45 QuickSmart Link connector 1x XLR mix out output 1x XLR thru output 1x IEC power connector
Full-color 1.9" LCD
Column: composite Pole: aluminum Sub: 15 mm plywood
Steel with black or white powder coat
Black or white
82.4" x 13.5" x 18.5" (2093 x 344 x 470 mm)
55.8 lbs (25.3kg)



EVOLVE 50M G2

8x 3.5" neodymium drivers
1x 12"
43 Hz – 20 kHz
37 Hz – 20 kHz
129 dB
120° x 40°
1500 W
4x XLR/TRS combo jack line / mic inputs 2x XLR/TRS combo jack for stereo line inputs 1x wireless stereo Bluetooth® audio input 1x stereo RCA input 1x 3.5 mm stereo input 1x 1/4" TRS HI-Z input 1x 1/4" footswitch input 1x RJ45 QuickSmart Link connector 1x XLR mix out output 1x XLR aux out output 1x IEC power connector
Full-color 2.9" LCD
Column: composite Pole: aluminum Sub: 15 mm plywood
Steel with black or white powder coat
Black or white
82.4" x 13.5" x 18.5" (2093 x 344 x 470 mm)
55.6 lbs (25.2 kg)



All content is subject to change without prior notice. All product imagery and/or renders are artistic digital illustrations and/or representations, and subject to change without prior notice. EV QuickSmart Mobile available in select countries. Apple, the Apple logo, iPhone®, iPad®, and App Store® are trademarks of Apple Inc., registered in the U.S. and other countries. Google Play and the Google Play logo are trademarks of Google LLC. *EVOLVE 30M / 30M G2 / 50 / 50 G2 / 50M / 50M G2 / 70 / 90 are available in select countries. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Electro-Voice Dynacord LLC is under license. Other trademarks and trade names are those of their respective owners. ¹Half-space measurement using live DSP preset. ²Maximum SPL is measured at 1 m using broadband pink noise at maximum output. ³Current rating is 1/8 power. ©2026 Electro-Voice Dynacord LLC